

The World's Smallest GigE PoE Camera

The Phoenix is a micro compact camera with a versatile board design, measuring only 24 x 24 mm and 28 x 28 mm. Its default shape resembles a traditional camera but can easily be transformed to best fit your application. It further advances industrial miniaturization with the compact NF-mount lens and the ix Industrial® Ethernet connector.







PHOENIX[™] The World's Smallest GigE PoE Camera

24 x 24 mm Models











C-mount with RJ45

C-mount with ix Connector

NF-mount with ix Connector

Model	MP	Resolution	FPS	Sensor	Format	Pixel Size	Shutter	Lens Mount	GigE Interface
PHX122S	12.2 MP	4024 x 3036 px	9.7 fps	Sony IMX226 CMOS	1/1.7″	1.85 µm	Rolling	С	RJ45 / ix
PHX050S-P PHX050S-Q	5.0 MP	2448 x 2048 px	24 fps	Sony IMX250MZR CMOS Sony IMX250MYR CMOS	2/3″	3.45 µm	Global	C/NF	RJ45 / ix
PHX050S	5.0 MP	2448 x 2048 px	24 fps	Sony IMX264 CMOS	2/3"	3.45 µm	Global	C/NF	RJ45 / ix
PHX032S	3.2 MP	2048 x 1536 px	38 fps	Sony IMX265 CMOS	1/1.8"	3.45 µm	Global	C/NF/S	RJ45 / ix
PHX023S	2.3 MP	1920 x 1200 px	52 fps	Sony IMX392 CMOS	1/2.3"	3.45 µm	Global	C/NF	RJ45 / ix
PHX016S	1.6 MP	1440 x 1080 px	77 fps	Sony IMX273 CMOS	1/2.9"	3.45 µm	Global	C/NF/S	RJ45 / ix
PHX004S	0.4 MP	728 x 544 px	291 fps	Sony IMX287 CMOS	1/2.9"	6.9 µm	Global	C/NF/S	RJ45 / ix

28 x 28 mm Models





C-mount with RJ45

Model	MP	Resolution	FPS	Sensor	Format	Pixel Size	Shutter	Lens Mount	GigE Interface
PHX200S	20.0 MP	5472 x 3648 px	6 fps	Sony IMX183 CMOS	1″	2.40 µm	Rolling	С	RJ45
PHX120S	12.3 MP	4096 x 3000 px	10 fps	Sony IMX304 CMOS	1.1"	3.45 µm	Global	С	RJ45
PHX089S	8.9 MP	4096 x 2160 px	13.7 fps	Sony IMX267 CMOS	1"	3.45 µm	Global	С	RJ45

For the latest Phoenix models and machine vision accessories, including NF-mount lenses and ix Industrial cables please visit www.thinklucid.com



NF-Mount Lens

The 5 MP lens is 40% smaller and up to 50% lighter while maintaining the same imaging performance as a standard C-mount lens.



Transformable

Transform any Phoenix camera. Get everything you need with our Phoenix Transform Kit for 90° and 180° shape configurations.



ix Industrial® Connector

70% smaller than a RJ45 socket. High EMC and vibration protection, positive locking hooks, locking force over 98 n, and guaranteed 5,000 mating cycles.



Polarization Models

See beyond visible light with the Phoenix camera featuring Sony's IMX250MZR/MYR CMOS polarized sensors. Models PHX050S-P/Q.